

ELIMAX FILTER & WATERFALL PUMPS

ELIMAX SERIES

CODE	MODEL	CABLE LENGTH	DRY/MOUNT FLOODED	DIMENSIONS (mm)			OUTLET	WATTS	VOLT	MAX FLOW Litres/Hr	MAX HD (Metres)
				Length	Width	Height					
14264	Elimax 500	10m	No	160	230	170	1/2"	11	240	700	1.25
14271	Elimax 1000	10m	No	160	230	170	1/2"	15		1200	1.45
14295	Elimax 2000	10m	No	160	230	170	1/2"	35		2200	2.20
14318	Elimax 4000	10m	No	200	310	200	1"	75		4100	2.90
14325	Elimax 6000	10m	No	200	310	200	1"	125		6100	3.90
14332	Elimax 9000	10m	No	200	310	200	1"	215		8800	5.20

ABOUT

These pond pumps are designed for use as water features and fountains. They are synchronous pond pumps, meaning the magnet rotor starts both clockwise and anticlockwise, depending on the current supply. The pumps are equipped with high quality, powerful magnets and a ceramic shaft. A flexible control flap (FFS technology) supports the water flow independently of the rotation direction. This makes the pumps highly efficient, as no "positively guided" rotation in one direction is stipulated, the motor and rotor system are not subjected to unnecessary strain.

APPLICATIONS

Water Features
Ponds
Fountains
Statues
Waterfalls
Pond Filters
Salt Water

KIT INCLUDES

Fountain Nozzles (vary depending on model)
Risers, adjustable tee piece & waterfall connections

FEATURES

Superior quality
Filter foam free design
Economical low wattage pump
Large filter cage



Head (m)	Approximate Flow Rate in Litres per Hour (Without Restriction)					
5.50						0 @ 5.3m
5.00						1786
4.50						2367
4.00					0 @ 3.9m	2926
3.50					2434	3456
3.25					2915	3957
3.00				0 @ 2.9m	3321	4444
2.50				1883	3678	4916
2.25			0 @ 2.2m	2189	3996	5365
2.00		0 @ 1.85m	1033	2459	4295	5808
1.50		163	1241	2706	4570	6229
1.25	0 @ 1.25m	461	1422	2935	4824	6643
1.00	416	709	1583	3151	5068	7049
0.50	567	925	1732	3544	5278	7444
0.25	693	1122	1871	3725	5522	7827
0.00	800	1300	2000	3900	5800	8200
MODEL	500	1500	2000	4000	6000	9000